

Providing the lowest temperatures in the industry without the freeze-ups



### Standard Features

- Fully enclosed system provides protection from outside contamination
- Factory insulated and jacketed ensures maximum efficiency
- Clamp-on return bends allow full access for cleaning and inspection
- \*Bottom to top ingredient/ marinade feed ensures complete liquid draining to virtually eliminate product waste or -
- \*Bottom to top giblet feed ensures complete liquid draining to virtually eliminate product waste

- Chiller is equipped with easily operated hand expansion/ liquid solenoid valve with single stage modulating evaporator pressure regulator
- Simple clean-in-place system makes sanitation easy
- Simple, easy-to-use controls monitor temperatures and settings
- Stainless steel supports allow for easy, secure mounting to floor or ceiling

### 24/7 Service & Parts Support

Contact a live Morris representative around the clock for field service or parts support at +1.919.582.9200.



\*Available in 2" [5cm] or 3" [7.6cm] diameter tubes

## Specifications

Model Number	Tube Length ft [m]
IC-S-08TT-C	8' [2.5]
IC-S-10TT-C	10' [3.1]
IC-S-16TT-C	16' [4.9]
IC-S-32TT-C	32' [9.8]

**S** - Sytem Type: LRA = Liquid Recirc. Ammonia, GLY = Glycol

**TT** - Number of Tubes

**C** - Connection size: 2 = 2", 3 = 3"

Typical unit lengths are shown. Unit dimensions based on customer requirements. Number of returns / tubes based on load.



Morris & Associates, Inc.  
803 Morris Drive | Garner, NC 27529  
Phone: 1.919.582.9200  
www.morris-associates.com

